SUPERSPEED CERTIFIED USB

LC-POWER

> 85% EFFICIENCY ErP 2014 COMPLIANT

Micro-ATX 2002MB

(incl. LC420-12 V2.31)

Case type:	Micro-ATX-Tower	Audio port:	HD Audio
Motherboard:	Micro-ATX, Mini-ITX	USB 3.0 port:	2
Drive bays 3.5" external:	1	USB 2.0 port:	-
Drive bays 5.25" external:	2	Barcode:	4260070124549
Drive bays 3.5" internal:	3	Case material:	metal
Drive bays 2.5" internal:	-	Mark of conformity:	CE
PCI slots:	4	Case colour:	black
Case fan standard/maximal:	0/3 (1x 80/92 + 1x 80 (lateral) + 1x 80/92/120 mm)	Front panel:	black
		Power supply integrated:	LC420-12 V2.31 (Efficiency > 85%)
Case dimensions h x w x d:	366 x 180 x 427 mm (total) 360 x 178 x 390 mm (cage)		
Graphic cards up to:	340 mm		
CPU cooler up to:	145 mm		
Weight (retail):	5,76 kg		

Characteristics: Incl. lateral ventilation slots on VGA and CPU level, power supply incl. 20+4 pin, 3x SATA, 1x PATA, 1x FDD, 1x 4+4 pin 12V, 1x PCI-Express 6 pin, 350W max., 120mm fan, Active PFC, efficiency > 85%, lockable (optional)

Note: USB 3.0 - internal mainboard connector